

Code SDS_EGGERTimber_en_US
Version 04
Release Date 05-23-2022

Safety Data Sheet

EGGER Timber

According to 29 CFR 1910.1200 App D

This product is not hazardous in the form in which it is shipped by the manufacturer, but may become hazardous by wood dust generating downstream activities (e.g. grinding, sanding, cutting or pulverizing).

Section 1: Identification of the substance/mixture and the company/undertaking

1.1 Product Identifier

Trade name EGGER sawn Timber

Product description Boards and planks cut from domestic conifer wood (spruce, scots pine)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use Building material for pallets, boxes, cable drums, concrete formwork, packaging,

Frame work (building material)

1.3 Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier/Importer EGGER Sägewerk GmbH

Im Kissen 19 59929 Brilon Germany

+49 2961 770-0

Regional Support Centre EGGER Wood Products LLC(US)

P.O. Box 907

Lexington, NC 27293 T+1-800-940-9633 environment@egger.com

Additional Information environment@egger.com

1.4 Emergency phone number

1-800-424-9300/+1703-527-3887 (Chemtrec)

Section 2: Hazards identification

2.1 Classification of the substance or mixture

OSHA HCS 2012 This product is generally an article and not hazardous, but is regulated under

OSHA for the release of wood dust during downstream activities, like grinding, sanding, cutting and sawing. The free formaldehyde levels are below OSHA reporting requirements. The classifications below are based upon wood dust:

Skin Irritation 2 Skin Sensitization 1 Eye Mild Irritation 2B Respiratory Sensitization 1

Specific Target Organ Toxicity Repeated Exposure 2: Respiratory Tract Irritation

Carcinogenicity 1A
Combustible Dust

2.2 Label elements

Labelling according to paragraph (f) 1910.1200; OSHA29 CFR



Hazard pictograms





Signal word DANGER

Hazard statements May form combustible dust concentrations in air

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H320 Causes eye irritation

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 May cause respiratory irritation H350 May cause cancer (inhalation)

H373 Causes damage to organs through prolonged or repeated exposure

(inhalation)

Precautionary statements P202 Do not handle until all safety precautions have been read and understood

P210 Keep away from heat/sparks/open flames/hot surfaces - no smoking

P260 Do not breathe dust

P271 Use only outdoors or in a well-ventilated area

P280 Wear protective gloves/protective clothing/eye protection

P302+P352+P305+P351+P338 On contact: Wash thoroughly with water P308+P337+P314+P340+ P264 If exposed or concerned: Get medical

advice/attention if you feel unwell, move to fresh air

2.3 Other hazards

Results of PBT and vPvB assessment

PBT Not applicable vPvB Not applicable

OSHA HCS 2012 This product is not considered hazardous under the U.S. OSHA 29 CFR

1910.1200 Hazard Communication Standard in the form in which it is shipped, but may become hazardous by wood dust generating downstream activities (e.g.

grinding, sanding, cutting or pulverizing).

NFPA Health=1, Flammability=1, Reactivity=0, Special Information=None

HMIS Health=1*, Flammability=1, Reactivity=0, PFE=E

*Chronic Health Hazard

E=Safety glasses, gloves, and a dust respirator

Section 3: Composition/information on ingredients

3.2 Chemical characterization: Mixtures (article)

Description The product composes of wood*.

*Wood contains trace amounts of various chemicals present in the environment, which are absorbed by trees through natural growth. A comprehensive listing of species is available upon request.

CALIFORNIA RESIDENTS:

WARNING: This product can expose you to chemicals including formaldehyde, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Section 4: First aid measures

4.1 Description of first aid measures

General information No special measures required regarding the product in the form it is shipped,

downstream activities like cutting, sawing or grinding can generate dust. To avoid health hazards while these downstream activities, take note of the following

measures:

Inhalation If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.



Skin Wash with plenty of soap and water. If skin irritation occurs: Get medical

advice/attention. Take off contaminated clothing and wash before reuse. After

contact with the molten product, cool rapidly with cold water

Eye Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eve irritation persists: Get medical

advice/attention.

Ingestion Rinse mouth thoroughly with water. Get medical attention if you feel unwell and

contact a poison control center or medical professional.

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 – Toxicological Information

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available

Section 5: Firefighting measures

5.1 Extinguishing media

Use firefighting measures that suit the environment

Fire-extinguishing powder

Carbon dioxide

Foam

5.2 Special hazards arising from the substance or mixture

Timber is a Class Acombustible material. If involved in a fire, product will burn.

Timber is not an explosion hazard. Sawing, sanding, or machining timber can result in the by-product wood dust. Wood dust may present a strong to severe explosion hazard if a dust cloud contacts an ignition source.

Airborne concentrations of 15 grams per cubic meter are often used as the lower explosive limit (LEL) for wood dusts.

OSHA interprets the explosive level as having no visibility within five feet or less.

In case of fire, the following gases can be released:

Carbon dioxide (CO2), Carbon monoxide (CO), Oxides of Nitrogen and other hazardous gases and particles

5.3 Advice for firefighters

Protective equipment Mouth respiratory protective device

Additional information Prevent formation of dust

Dispose of fire debris and contaminated firefighting water in accordance with official regulations.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions Do not breathe dust.

Emergency Procedures No emergency procedures are expected to be necessary if material is used under

ordinary conditions as recommended.

6.2 Environment precautions

No special measures required

6.3 Methods and material for containment and cleaning up

Not applicable for product in purchased form. Dust generated from sawing, sanding, drilling or routing this product may be vacuumed or shoveled for recovery or disposal. Wood dust clean-up and disposal activities should be accomplished in a manner to minimize of airborne dust.

Dispose of the material collected according to regulations

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment

See Section 13 for disposal information

Section 7: Handling and storage

7.1 Precautions for safe handling

Use good safety and industrial hygiene practices. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Wear a respiratory mask if using hand tools without a dust extraction device. Observe all liability insurance association regulations for commercial processing operations (e.g. safety goggles).



Information on protection against explosions and fires: Avoid formation of dust

7.2 Conditions for safe storage, including any incompatibilities

Storage

No special precautions for handling product. Use good safety and industrial hygiene practices. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.

Keep away from ignition sources

7.3 Specific end use(s)

No further relevant information available

Section 8: Exposure controls/personal protection

8.1 Control parameters

Wood dust needs to be controlled while cutting, sawing, drilling or other dust generating processes are performed.

8.2 Exposure controls

·	Result	ACGIH 2007	NIOSH	OSHA
Wood dust	TWAs	1mg/m³ TWA	1mg/m³ TWA	15mg/m³, total
		As Wood dust, all soft	As Wood dust, all soft and	dust(5mg/m³, respirable
		and hard w oods	hard w oods	fraction)
				(as nuisance dust)
Formaldehyde	TWAs	0.3ppm TLV	0.016ppm TWA, 0.1ppm	0.75ppm TWA, 2ppm
(50-00-0)			Ceiling (15 minutes)	STEL, 0.5ppm action level

Engineering measures/controls

Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Due to the explosive potential of wood dust when suspended in air, precautions should be taken during sanding, sawing or machining of wood products to prevent sparks or other ignition sources in ventilation equipment. Use of totally enclosed motors is recommended.

Personal Protective Equipment Pictograms





Respiratory

Eye/Face Hands Skin/Body

General Industrial Hygiene Considerations

Environmental Exposure Controls

where airborne dust levels exceed appropriate PELs and TLVs Wear safety glasses Wear protective gloves Rubberized doth, canvas or leather gloves

Use of a NIOSH/MSHA approved dust respirator is recommended

Wear long sleeves and/or protective coveralls.

Practice good housekeeping and avoid creating/breathing dust. Do not allow dust to collect. Waintain, clean, and fit test respirators I accordance with OSHA regulations.

No data available

Section 9: Physical and chemical properties

9.1 Information on basic p	ohysical and chemical	properties	
Physical State	solid	Evaporation rate	Not relevant
Color	differs	Partitions coefficient	Not relevant

Flammability D, d0, s2 (DIN EN 14081-1) Autoignition differs 0.13 W/mK (EN12523) Odor Decomposition temperature



Vapor Pressure	Not relevant	Viscosity	No data available
Odor threshold	Not relevant	Burning time	No data available
Vapor density	No data available	Density	approx 460-520kg/m³ (EN350-2)
рН	Not relevant	Oxidizing properties	No data available
Relative density	Not relevant	Explosive limits	No data available
Melting point	Not relevant	Flash point	Not relevant
Freezing point	Not relevant	Boiling point	Not relevant
Solubility	Not soluble in water		

9.2 Other information

No further relevant information available.

Section 10: Stability and reactivity

10.1 Reactivity

The product is not reactive under normal conditions of use, storage and transport.

10.2 Chemical stability

Stable under recommended storage conditions

Conditions to be avoided: No decomposition if used according to specifications

10.3 Possibility of hazardous reactions

No dangerous reactions known

10.4 Conditions to avoid

Exposure to water, ignition source, high relative humidity and high temperature

10.5 Incompatible materials

Incompatible Materials: acids (strong), Oxidizers (strong)

10.6 Hazardous decomposition products

Hazardous decomposition may occur thermal and/or thermal oxidative decomposition can produce irritating and toxic fumes and gases.

Section 11: Toxicological information

11.1 Information on toxicological effects

Other Material	Not applicable for product in purchased from.	. Individual component information is provided

below if available

Components

Formaldehyde 50-00-0 Acute Toxicity: Ingestion/Oral-RatLD50 > 200mg/kg; Inhalation-RatLD50

	0.578mg/l/4h			
GHS Properties	Classification			
Acute toxicity	OSHA HCS 2012 – Acute Toxicity – Data lacking (Oral, dermal, inhalation)			
Aspiration hazard	OSHA HCS 2012 – Data lacking			
Carcinogenicity	OSHA HCS 2012 Carcinogenicity 1A			
Germ Cell Mutagenicity	OSHA HCS 2012 – Data lacking			
Skin corrosion/Irritation	OSHA HCS 2012 – Skin Irritation 2			
Skin sensitization	OSHA HCS 2012 – Skin Sensitizer1			
STOT-RE	OSHA HCS 2012 – Specific target Organ Toxicity Repeated Exposure 2			
STOT-SE	OSHA HCS 2012 – Specific target Organ Toxicity Single Exposure 3: respiratory Tract Irritation			
Toxicity for Reproduction	OSHA HCS 2012 – Data lacking			
Respiratory sensitization	OSHA HCS 2012 – Respiratory Sensitizer 1			
Serious eye damage/Irritation	OSHA HCS 2012 - Eye Mild Irritation 2B			
-				

Target Organs Skin/dermal. Lungs, Respiratory System

Route(s) of entry/exposure Inhalation, Skin, eye

Medical Conditions Dusts may aggravate as thma or other respiratory disorders.

SDS_EGGERTimber_en_US.04



Aggravated by Exposure

Potential Health Effects

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs include:

Inhalation

Acute(Immediate) May cause respiratory irritation

Chronic (Delayed) Repeated and prolonged exposure may cause cancer. Repeated and prolonged exposure

may cause sensitization of the respiratory system.

Skin

Acute(Immediate) May cause irritation

Chronic(Delayed) Repeated and prolonged exposure may cause sensitization

Eye

Acute (Immediate) May cause irritation Chronic(Delayed) No data available

Ingestion

Acute(Immediate) Under normal conditions of use, no health effects are expected. Chronic(Delayed) Under normal conditions of use, no health effects are expected.

Carcinogenic

Effects

Carcinogenic Effects Wood dust is listed by NTP known to be a Human Carcinogen(10th Report), IARC

Monographs: Wood dust, group 1 – IARC Group 1: Carcinogenic to humans; sufficient evidence of carcinogenicity. This classification is primarily baes on studies showing an association between occupational exposure to wood dust and adenocarcinoma of the nasal cavities and paranasal sinuses. IARC did not find sufficient evidence of an association between occupational exposure to wood dust and cancers of the hypopharynx, oropharynx,

lymphatic and hematopoietic systems, lungs, stomach, colon or rectum.

		/ 1	1 , 0	*	
		CAS	OSHA	IARC	NTP
1	Wood dust as Wood dust, all soft	Not Available	Not listed	Group 1 – Carcinogenic	Know n Human Carcinogen
	and hard w oods				
	Formaldehyde	50-00-0	Specifically Regulated	Group 1 – Carcinogenic	Known Human Carcinogen
			Carcinogen		

Section 12: Ecological information

12.1 Toxicity

Formaldehyde: EC50 5.8mg/l/48h (Daphnia magna)

Not applicable for particleboard/MDF

12.2 Persistence and degradability

No further relevant information available

12.3 Bioaccumulative potential

Formaldehyde: log POw: 0.35 Not applicable for particleboard/MDF

12.4 Mobility in soil

No further relevant information available

Generally not hazardous for water

12.5 Results of PBT and vPvB assessment

PBT Not applicable Other adverse effects Not applicable

12.6 Other adverse effects

No further relevant information available

Section 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Disposal according to local regulations

Uncleaned packaging Dispose of packaging according to regulations on the disposal of packaging



recommendations

Section 14: Transport information

14.1 UN-number
ADR, ADN, IMDG, IATA
Void
14.2 UN proper shipping name
ADR, ADN, IMDG, IATA
Void
14.3 Transport hazard class(es)
ASR, ADN, IMDG, IATA class
Void
14.4 Packing group
ADR, IMDG, IATA
Void

14.5 Environmental hazards

Not applicable

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC CodeNot applicable

UN "Model Regulation"

Void

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

NPCA-HMIS® III				
Category	Rating	Description		
Chronic	*			n repeated overexposure (dust)
Health	0	No significant risk		
Flammability	1	Material that require considerable preheating, under all ambient temperature conditions, before ignition and combustion can occur		
Physical Hazard	0	Material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive		
Personal protection	-	wa.o., po.jo., accompace, contaction, of control of		
NFPA® 704				
Category	Degree of hazard	Description		
Flammability	Flammability 1 Material that require considerable preheating, under all ambient temperature conditions, before ignition and combustion can occur			
Health	0	Material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material		
Instability	0		mallystable, even under fire co	onditions
Special hazard				
SARA Hazard Classifications Inventory		Acute, Chronic		
Component	CAS		Canada DSL	TSCA
EGGER Timber	Not ap	plicable	Not listed. All components are on the Canada DSL or are excluded from listing or below de minimis reporting	Not listed. All components are on the TSCA inventory or are excluded from listing or below de minimis reporting

N/A

N/A

50-00-0

Not listed

Not listed

B1, D1A, D2A, D2B

Formaldehyde

Canada – WHMIS – Classifications of Substances EGGER Timber and ingredients (unless listed below)

Canada – WHMIS – Ingredient Disclosure List EGGER Timber and ingredients (unless listed below)

MORE FROM WOOD.



Formaldehyde 50-00-0 0.1% (concentration in product is below de Minimis) U.S.-OSHA - Process Safety Management - Highly hazardous Chemicals EGGER Timber and ingredients (unless listed below) N/A Not listed Formaldehvde 50-00-0 1000lb TQ Environment U.S. - CERCLA - Hazardous Substances EGGER Timber and ingredients (unless listed below) N/A Not listed Formaldehyde 50-00-0 100lb final RQ U.S. - CERCLA/SARA - Section 304 EHS RQ EGGER Timber and ingredients (unless listed below) N/A Not listed Formaldehyde 50-00-0 100lb EPCRARQ U.S. - EPCRA -Section 302 (EHS) TPQ EGGER Timber and ingredients (unless listed below) N/A Not listed Formaldehyde 50-00-0 500lb TPQ U.S. - EPCRA - Section 313 - Toxic Chemicals EGGER Timber and ingredients (unless listed below) N/A Not listed Formaldehyde 50-00-0 0.1% (concentration in product is below de Minimis) United States - California Environment U.S. - California - Proposition 65 - Carcinogens List EGGER Timber and ingredients (unless listed below) N/A Not listed Formaldehyde 50-00-0 carcinogen, NSRL 40µg/day Wood dust as Wood dust, all soft and hard woods N/A carcinogen

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out

Section 16: Other information

This information is based on our present knowledge and comes from sources believed to be accurate or otherwise technically correct. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Initial release 08-13-2018 Last Revision Date 05-23-2022